

NVR SERIES

Provision-ISR conventional NVRs are intended for obtaining video streams from the IP cameras via the IP networks for the purpose of their storage and subsequent playback. These devices communicate with the IP cameras through the general network, without the need of direct IP camera connection, providing the installer with the highest flexibility in the design of the system and the wiring.




NVR5-4100X+(MM)

4CH 5MP NVR

Provision-ISR NVR5-4100X+(MM) is an easy-to-install solution suitable for small-sized installations (up to 4 channels).

The device, available in the elegant mini metal case, provides you with everything you need for a trouble-free CCTV project.



MAIN FEATURES

- Channels: 4
- Video output: HDMI / VGA (1080P, 1280x1024, 1024x768)
- Max. Recording: 4CH 5MP Real Time
- HDD: 1 SATA (6 TB Max)
- Alarms: None - IPC Inputs/outputs only
- Audio: IN IPC inputs only - OUT IPC outputs only
- Video Analytics: Yes (Must be supported by IPC)



SPECIFICATIONS

Video	Input	4CH Over Network
	Output	HDMI / VGA (1080P, 1280x1024, 1024x768)
	Decoding Format	H.265 / H.264
	Decoding Capabilities	1Ch - 5MP ; 4Ch - D1
Audio	Analytics Channels	Camera Tampering, Line Crossing, Sterile Area, Object Monitoring
	Input	Depends on Camera Inputs
	Output	Depends on Camera Outputs
	Two Way Audio	No
Bandwidth	Incoming	32Mbps
	Outgoing	32Mbps
Recording	Real-Time Recording	4CH 5MP Real-Time
	8MP	No
	5MP	120FPS (NTSC)/100FPS (PAL)
	4MP	120FPS (NTSC)/100FPS (PAL)
	3MP	120FPS (NTSC)/100FPS (PAL)
	2MP (1080P)	120FPS (NTSC)/100FPS (PAL)
	1.3MP (960P) and lower	120FPS (NTSC)/100FPS (PAL)
	Recording Modes	Schedule, Manual, Motion, Sensor, Analytics
Playback	Playback Channels	4CH
	Search Mode	Time-Slice, Time, Event, File Management
Backup	USB	2 USB 2.0 Port
	DVD Burner	No
	Backup Format	AVI/DAT

SPECIFICATIONS

Remote Application	Master Stream	Up to 4CH@Recording Resolution
	Sub-Stream	Depends on IPC
	Browser	Safari (Mac OS) IE (Windows Vista/7/8/10)
	CMS	Yes
	Mobile Application	Provision CAM2 for iOS/Android
	User Access	5 Users Online with Professional Authority Management
Alarm	Input	Depends on Camera
	Output	Depends on Camera
Storage	HDD	1 SATA (6TB)
	E-SATA	No
PTZ	Whitnection	Via Network
	Supported Whittrols	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
	RS-485	No
Network	Ethernet	100 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P, RTSP
	ONVIF	Yes
	Ports	No
PoE	Interface	No
	Standard	No
	Total Power	No
	Max. Power Output (Per Ch.)	No
	Power Supply	DC12V/2A
Others	Power Whitsumption (No HDD)	5W
	Dimention	W255xD220xH45mm
	Operation Temperature	0°C ~50°C